




KENNEDY VALVE

**2-1/2" - 12" R/S NON-RISING
FLANGED GATE VALVES
GENERAL DIMENSIONS**

NOTE:
CONFORMS TO DIMENSIONAL, MATERIAL & TEST REQUIREMENTS 350 PSI RATING
AWWA C515 - MODEL 'KS-RW'
AWWA C509 - MODEL 'KS-FW' IN DUCTILE
ASME B16.1 CLASS 125 FLANGES

MODEL 5561A (w/ HANDWHEEL)
MODEL 5701A (w/ POST PLATE)
MODEL 5561AN (w/ NUT)



ALL FLANGE VALVES TAPPED & PLUGGED @ POSITION "A"

Nominal Size In's	Clear Dia H	No. of Turns to Open	Valve Dimensions				Flanges & Flange Drilling to ANSI B16.1						
			A	-	E	H' Whl O.D.	Flange O.D. CØ	Flange Thick D	B.C. DIA k	Size of Bolts FØ	No. of Bolts F#	Weight lb	
-	-	-	-	-	-	-	-	-	-	-	-	-	-
2-1/2"	2.50"	5	7.50"	-	11.38"	7.25"	7.00"	0.69"	5.50"	5/8"	4	49	
3	3.00"	10	8.00"	-	12.38"	10.00"	7.50"	0.69"	6.00"	5/8"	4	62	
4	4.25"	13	9.00"	-	14.75"	10.00"	9.00"	0.94"	7.50"	5/8"	8	87	
6	6.25"	19	10.50"	-	19.00"	12.00"	11.00"	1.00"	9.50"	3/4"	8	134	
8	8.25"	25	11.50"	-	22.50"	14.00"	13.50"	1.12"	11.75"	3/4"	8	205	
10	10.25"	31	13.00"	-	26.50"	18.00"	16.00"	1.18"	14.25"	7/8"	12	331	
12	12.25"	37	14.00"	-	30.00"	18.00"	19.00"	1.25"	17.00"	7/8"	12	515	